



US010341943B2

(12) **United States Patent**
Gupta et al.

(10) **Patent No.: US 10,341,943 B2**

(45) **Date of Patent: Jul. 2, 2019**

(54) **METHOD AND APPARATUS FOR
DISCOVERING NEIGHBORHOOD
AWARENESS NETWORKING DEVICES
USING A SURROGATE DEVICE**

70/1262 (2018.01); Y02D 70/142 (2018.01);
Y02D 70/144 (2018.01); Y02D 70/146
(2018.01); Y02D 70/164 (2018.01); Y02D
70/166 (2018.01); Y02D 70/22 (2018.01);
Y02D 70/26 (2018.01)

(71) Applicant: **Motorola Mobility LLC**, Chicago, IL
(US)

(58) **Field of Classification Search**

CPC H04W 4/206; H04W 8/00; H04W 8/005;
H04W 48/14; H04W 48/16; H04W 48/18;
H04W 52/02; H04W 52/0209; H04W
52/0219; H04W 52/0229; H04W 56/00;
H04W 56/001

(72) Inventors: **Ranjeet Gupta**, Chicago, IL (US);
Gabriel Burca, Palatine, IL (US);
Mary Hor-Lao, Chicago, IL (US);
Binesh Balasingh, Naperville, IL (US)

See application file for complete search history.

(73) Assignee: **MOTOROLA MOBILITY LLC**,
Chicago, IL (US)

(56)

References Cited

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 109 days.

7,864,744 B2 * 1/2011 Song H04W 72/02
370/338
9,049,578 B2 * 6/2015 Abraham H04W 4/206
9,125,124 B2 * 9/2015 Dwivedi H04W 36/0083
9,258,193 B2 * 2/2016 Kasslin H04L 41/12
9,398,437 B2 * 7/2016 Kasslin H04L 45/745
9,439,147 B2 9/2016 Huang
9,480,013 B2 * 10/2016 Fang H04W 48/16
(Continued)

(21) Appl. No.: **15/219,723**

(22) Filed: **Jul. 26, 2016**

(65) **Prior Publication Data**

US 2018/0035363 A1 Feb. 1, 2018

Primary Examiner — Hashim S Bhatti

(51) **Int. Cl.**

H04W 48/16 (2009.01)
H04W 8/00 (2009.01)
H04L 29/08 (2006.01)
H04W 64/00 (2009.01)
H04W 52/02 (2009.01)
H04W 88/04 (2009.01)

(57)


ABSTRACT

A first communication device performs a method that includes detecting a common network connection with a second communication device. The method further includes determining to perform neighborhood awareness networking scanning on behalf of the second communication device. When the first communication device detects a neighborhood awareness networking transmission while performing the neighborhood awareness networking scanning, it notifies the second communication device and discontinues the scanning on behalf of the second communication device.

(52) **U.S. Cl.**

CPC **H04W 48/16** (2013.01); **H04L 67/16**
(2013.01); **H04W 8/005** (2013.01); **H04W**
52/0229 (2013.01); **H04W 64/003** (2013.01);
H04L 67/12 (2013.01); **H04L 67/18** (2013.01);
H04W 88/04 (2013.01); **Y02D 70/00**
(2018.01); **Y02D 70/1242** (2018.01); **Y02D**

20 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

9,554,344	B2	1/2017	Huang et al.	
9,578,626	B2 *	2/2017	Sadasivam	H04W 72/0406
9,693,217	B2 *	6/2017	Kasslin	H04W 8/005
9,763,190	B2 *	9/2017	Abraham	H04W 52/0225
9,801,039	B2	10/2017	Oren	
9,820,117	B1 *	11/2017	Tran	H04W 4/206
2017/0019853	A1	1/2017	Ghosh et al.	
2017/0347359	A1	11/2017	Yang et al.	
2018/0027366	A1	1/2018	Fujimori et al.	

* cited by examiner




FIG. 1

200




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

1

METHOD AND APPARATUS FOR DISCOVERING NEIGHBORHOOD AWARENESS NETWORKING DEVICES USING A SURROGATE DEVICE

FIELD OF THE DISCLOSURE

The present disclosure relates generally to wireless communication and more specifically to discovering neighborhood awareness networking communication devices using a surrogate neighborhood awareness networking device.

BACKGROUND

The popularity of proximity-based social and mobile services has grown significantly over the last few years, and the expectation is that it will continue to do so for the foreseeable future as the mobile ecosystem evolves. To meet demand for such services, neighborhood awareness networking (NAN) technology, such as Wi-Fi Aware™, was developed. A NAN protocol allows for the bidirectional sharing of information directly between nearby or proximate NAN devices without the need for an intermediary device such as a base station, access point, router, or other infrastructure device and without the need for a network connection. Accordingly, a NAN protocol is a proximity-based protocol that provides for transmissions and scanning procedures which facilitate NAN devices discovering other NAN devices within range or proximity, wherein a discovered NAN device, for instance, offers information or a service meeting a specified criteria.

One shortcoming relates to the current mechanism for locating or discovering other NAN devices within range. To do this, for instance using Wi-Fi Aware™, NAN devices continuously transmit NAN discovery beacon frames while also scanning for the NAN discovery beacon frames of other NAN devices. However, the transmission of and scanning for NAN discovery beacon frames comes at a power cost. In some cases, measurements and estimates show and predict that transmitting and scanning for NAN discovery beacon frames can account for approximately 50% of a mobile device's average power consumption over the course of a day.

BRIEF DESCRIPTION OF THE FIGURES

The accompanying figures, where like reference numbers refer to identical or functionally similar elements throughout the separate views, form part of the specification and illustrate embodiments in accordance with the included claims.

FIG. 1 shows a first communication device performing a surrogate NAN scanning role to scan for NAN communication devices on behalf of a second communication device, in accordance with some embodiments.

FIG. 2 shows a block diagram of a NAN communication device with internal components, in accordance with some embodiments.

FIG. 3 shows a logical flow diagram illustrating a method for a first communication device to perform NAN scanning on behalf of a second communication device, in accordance with some embodiments.

FIG. 4 shows a logical flow diagram illustrating a method performed by the second communication device for suppressing NAN scanning while the first communication device performs NAN scanning on its behalf, in accordance with some embodiments.

2

FIG. 5 shows a schematic diagram of a first communication device performing NAN scanning on behalf of a second communication device and the second communication device suppressing NAN scanning, in accordance with some embodiments.

FIG. 6 shows a schematic diagram of a first communication device suppressing NAN scanning, in accordance with some embodiments.

Skilled artisans will appreciate that elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help to improve understanding of embodiments of the present teachings. In addition, the description and drawings do not necessarily require the order presented. It will be further appreciated that certain actions and/or steps may be described or depicted in a particular order of occurrence while those skilled in the art will understand that such specificity with respect to sequence is not actually required.

The apparatus and method components have been represented, where appropriate, by conventional symbols in the drawings, showing only those specific details that are pertinent to understanding the embodiments of the present teachings so as not to obscure the disclosure with details that will be readily apparent to those of ordinary skill in the art having the benefit of the description herein.

DETAILED DESCRIPTION

Generally speaking, pursuant to various embodiments described herein, the present disclosure provides a method and apparatus for the discovery of NAN communication devices. More specifically, a first communication device and a second communication device share a common network connection. The first communication device includes at least one network interface coupled to a processor (also referred to herein as a processing element). The network interface is to form the common network connection with the second communication device and to receive a NAN transmission. The processor is to determine to perform a surrogate NAN scanning role relative to the second communication device (which correspondingly performs a subordinate NAN scanning role), detect the NAN transmission while performing the surrogate scanning role, and notify the second communication device and determine to discontinue the surrogate scanning role in response to detecting the NAN transmission.

Thus, in accordance with described embodiments, suppressing NAN scanning can provide the second communication device the benefit of power savings over executing unsuppressed NAN scanning. This benefit is enhanced when, for example, the second communication device has a lower power capability, e.g., less battery charge, lack of access to an alternating current (AC) power source, etc., relative to the first communication device.

NAN communication devices, also referred to simply as communication devices or NAN devices, are electronic devices configured to operate in accordance with a NAN protocol, such as Wi-Fi Aware™, by sending and scanning for NAN transmissions, such as NAN discovery beacon frames, NAN synchronization beacon frames, and NAN service discovery frames, in order to discover other NAN devices. NAN discovery beacon frames are also referred to simply as discovery beacon frames. A non-exhaustive list of electronic devices which can operate as NAN devices includes smartphones, phablets, tablets, laptops, e-book

readers, portable media players, portable gaming devices, athletic monitoring devices, GPS navigation devices, desktop computers, and servers.

FIG. 1 shows a NAN device **102** having a common network connection with a NAN device **104**; wherein a first, e.g., **104**, of these two NAN devices performs scanning, on behalf of a second, e.g., **102**, of these two NAN devices, to discover other NAN devices. Communication devices having a common network connection means that the communication devices are, during some time period, simultaneously connected to the same network.

For one example, the NAN devices **102** and **104** have a common network connection by virtue of a direct wireless link **106** formed between the devices, such that the devices can communicate without using an intermediary device. The direct link **106** can be formed, for instance, using a wireless peer-to-peer (P2P) technology, such as Miracast, LTE-Direct, WiFi-Direct, Tunneled Direct Link Setup, Bluetooth low-energy (BLE), or any other suitable technology that enables establishing direct wireless links.

For another example, the NAN devices **102** and **104** have a common network connection by virtue of the devices both being connected to a same wireless network **130** such that the devices can communicate using an intermediary device, such as a base station or access point. As a particular illustration, the NAN devices **102** and **104** can have a common network connection when the NAN device **102** forms a wireless link **124** with an access point **122** within the Wi-Fi network **130** during a same time period that the NAN device **104** forms a wireless link **126** with the access point **122**.

For another example, the NAN devices **102** and **104** have a common network connection by virtue of a wired connection, such as a USB connection, between the devices **102**, **104**. For another example, the NAN devices **102** and **104** have a common network connection by virtue of direct communications between the devices using another protocol such as, a NAN protocol, a near-field communication (NFC) protocol, or another short-range wireless communication protocol. For another example, the NAN devices **102** and **104** have a common network connection by virtue of the devices both being connected to the network **130** using a different type of wireless communication technology such as a cellular technology or a different wireless local area technology (WLAN) technology. Additionally, the NAN devices **102** and **104** can have a common network connection by virtue of the devices being connected using any other suitable ad hoc or non-ad hoc wireless technology.

Also shown are three NAN devices **110**, **112**, **114** operating in a NAN cluster **108** and an isolated NAN device **128** not belonging to a NAN cluster. The NAN devices **102**, **104**, **110**, **112**, **114**, and **128** are configured to implement a NAN protocol by which these devices **102**, **104**, **110**, **112**, **114**, **128** transmit NAN discovery beacon frames and scan for NAN discovery beacon frames transmitted by other NAN devices to facilitate the discovery of NAN devices and NAN clusters. For a particular embodiment, the NAN devices **102**, **104**, **110**, **112**, **114**, and **128** are configured in accordance with the "Neighbor Awareness Networking Technical Specification," Version 1.0, hereinafter "NANTSv1.0," issued by the Wi-Fi Alliance with regard to its Wi-Fi Aware™ program to transmit and scan for NAN discovery beacon frames, which are modified IEEE 802.11 beacon management frames. A more detailed description of a NAN device transmitting NAN discovery beacon frames and scanning for NAN discovery beacon frames is provided by reference to FIG. 5.

Turning momentarily to FIG. 5, a second **504** of two pictured presentations **502** and **504** shows the NAN device **102** transmitting NAN discovery beacon frames **582** and performing NAN scanning **584** between the transmissions of the NAN discovery beacon frames **572**. Presentation **504** also shows the NAN device **104** transmitting NAN discovery beacon frames **572** and performing NAN scanning **574** between the transmissions of the NAN discovery beacon frames **572**. Using the presentation **504**, the NAN device **102** performing unsuppressed NAN scanning **584** and unsuppressed transmitting of the NAN discovery beacon frames **582** is described next in detail. This description also applies to the NAN device **104** performing unsuppressed NAN scanning **574** and unsuppressed transmitting of the NAN discovery beacon frames **572**, although a similar detailed description is not repeated for brevity.

As used herein, a time interval between consecutive NAN discovery beacon frames transmitted by the same NAN device is referred to as an "interframe time interval." An interframe time interval for the NAN discovery beacon frames **582** is indicated in presentation **504** at **586**. The NANTSv1.0 specifies a time between consecutive NAN discovery beacon frames transmitted by the same NAN device of between 50 time units (TUs) and 200 TUs. However, for some embodiments, the interframe time interval is longer than 200 TUs.

For some embodiments, a TU is an arbitrary unit of time that indicates a relative relationship between times specified herein and/or with times indicated in TUs appearing within the NANTSv1.0 and other technical specifications directed to NAN operations. In other embodiments, a TU represents 1024 microseconds, in accordance with one or more of the Institute of Electrical and Electronics Engineers (IEEE) 802.11 standards. For a particular embodiment, a TU is equivalent to a millisecond.

Indicated at **588** is a scanning time interval for the NAN device **102**. A scanning time interval is the length of time a NAN device scans for NAN discovery beacon frames of other NAN devices between transmissions of its own NAN discovery beacon frames. In presentation **504**, for example, the NAN devices **102** and **104** continuously scan **584**, **574**, respectively, for NAN discovery beacon frames of other NAN devices from the termination of its own NAN discovery beacon frame **582**, **572**, respectively, to the beginning of its next NAN discovery beacon frame.

The NAN discovery beacon frames **582** and **572** make the NAN devices **102** and **104** discoverable to the NAN device **128**, provided that the NAN device **128** is performing NAN scanning and is within range to receive the NAN discovery beacon frames **582** and **572**. Similarly, the NAN devices **102** and **104**, while scanning **584**, **574**, discover the NAN device **128** when the devices **102**, **104** receive NAN discovery beacon frames from the NAN device **128**.

Carried within NAN discovery beacon frames are NAN information elements (IEs). Furthermore, NAN attributes are incorporated in the NAN IEs, which, for some embodiments, adhere to a vendor-specific implementation. Each NAN device can both generate NAN IEs for transmission and decode received NAN IEs. A NAN IE carried by a NAN discovery beacon frame received from the NAN device **128** communicates to the NAN device **102** or **104** a service and/or information being sought or offered by the NAN device **128**. If the service and/or information being sought or offered by the NAN device **128** is being offered or sought, respectively, by the NAN device **102** or **104** then the NAN device **102** or **104** form a direct connection with the NAN device **128** using a protocol sufficient to provide the service

5

and/or information. The direct connection, using, for example, Wi-Fi direct or some other P2P, occurs without the need for local area network (LAN) or wide area network (WAN) infrastructure.

Individual NAN devices which have discovered one another can also group into a NAN cluster. A NAN cluster is a collection of NAN devices that share a common set of NAN parameters and are synchronized to the same discovery window schedule, for instance as specified in the NANTSv1.0. The NAN devices **110**, **112**, **114** of the NAN cluster **108** send and receive NAN transmissions between themselves, as indicated at **116**, **118**, and **120**. Using the transmissions, the NAN devices **110**, **112**, **114** participate in a NAN master device selection procedure, which is based on a relative ranking of parameters between the NAN devices **110**, **112**, **114**. The NAN device elected as master, taken to be the NAN device **110**, controls the timing of cluster **108** operations. The subordinate NAN devices **112** and **114** synchronize with the master NAN device **110** to determine the discovery window schedule and the timing of NAN synchronization beacon frames.

All of the NAN devices **110**, **112**, **114** operating in the NAN cluster **108** transmit and receive NAN service discovery frames to communicate available services and information. Only the master NAN device **110**, however, transmits NAN discovery beacon frames. The subordinate NAN devices **112**, **114** discontinue transmitting NAN discovery beacon frames until such time as they assume the role of the master device or are no longer participating in the NAN cluster **108**. The NAN cluster **108** is discoverable to the NAN devices **102** and **104** by NAN discovery beacon frames being transmitted by the master NAN device **110**.

FIG. 2 shows a block diagram of a NAN device **200** in accordance with embodiments of the present teachings. For a particular embodiment, the NAN device **200** represents the NAN devices **102** and **104**. Included within the NAN device **200** is: a NAN transceiver **202**; a processing element or processor **204**; memory **206**; an alternate network interface **208**; a power supply **210**; and a user interface **212**, which are all operationally interconnected by internal connections, such as a bus **214**.

A limited number of device components **202**, **204**, **206**, **208**, **210**, **212**, **214** are shown within the NAN device **200** for ease of illustration. Other embodiments may include a lesser or greater number of components in a NAN device. Moreover, other components needed for a commercial embodiment of a NAN device that incorporates the components **202**, **204**, **206**, **208**, **210**, **212**, **214** shown for the NAN device **200** are omitted from FIG. 2 for clarity in describing the enclosed embodiments.

In general, one or more of the device components **202**, **204**, **206**, **208**, **210**, **212**, **214** are configured with functionality in accordance with embodiments of the present disclosure as described herein with respect to the remaining figures. “Configured,” “adapted,” “operative,” or “capable,” as used herein, means that indicated components are implemented using one or more hardware elements, which may or may not be programmed with software and/or firmware, as the means for the indicated components to implement their desired functionality. For an example, at least one of the components **202**, **204**, **206**, **208**, **210**, **212**, **214** can be configured through executing algorithms consistent with the diagrams shown in FIGS. 3, 4, 5 and 6 and the accompanying description.

For one embodiment, the NAN device **104** uses one or more of the components **202**, **204**, **206**, **208**, **210**, **212**, **214** to perform a method for NAN scanning on behalf of another

6

NAN device, such as the NAN device **102**, for instance, as described below by reference to FIG. 3. The method includes detecting a common network connection with a second communication device. The method further includes determining to perform NAN scanning on behalf of the second communication device and detecting a NAN transmission while performing the NAN scanning. The method also includes notifying the second communication device and discontinuing the NAN scanning on behalf of the second communication device in response to detecting the NAN transmission.

For another embodiment, the NAN device **102** uses one or more of the components **202**, **204**, **206**, **208**, **210**, **212**, **214** to perform a method for suppressing NAN scanning to allow NAN scanning on its behalf by another NAN device, such as the NAN device **104**, for instance as described below by reference to FIG. 4. The method includes detecting a common connection with a first communication device and suppressing NAN scanning. The method further includes receiving a notification from the first communication device, wherein the notification indicates a detected NAN transmission, and discontinuing the suppressing of the NAN scanning in response to receiving the notification.

More particularly regarding the operation of the components **202**, **204**, **206**, **208**, **210**, **212**, **214**, the processing element **204**, for instance, includes arithmetic logic and control circuitry necessary to perform the digital processing, in whole or in part, for the NAN device **200** to perform surrogate NAN scanning on behalf of another NAN device or for the NAN device **200** to suppress NAN scanning while performing a subordinate NAN scanning role, in accordance with described embodiments for the present teachings. For one embodiment, the processing element **204** represents a primary microprocessor, also referred to as a central processing unit (CPU), of the NAN device **200**. For example, the processing element **204** can represent an application processor of a tablet. In another embodiment, the processing element **204** is an ancillary processor separate from the CPU, for instance included within or used with the NAN transceiver **202** or the alternate network interface **208**, wherein the ancillary processor is dedicated to providing the processing capability, in whole or in part, needed for the components **202**, **206**, **208**, **210**, **212**, **214** of the NAN device **200** to perform at least some of their intended functionality.

For example, the processing element **204** performs NAN functionality by implementing a NAN protocol to transmit and scan for NAN transmissions. For a particular embodiment, the processing element **204** implements a NAN discovery engine that creates, decodes, and filters NAN discovery frames such as NAN discovery beacon frames and NAN service discovery frames. The processing element **204** further implements a NAN medium access control (MAC) protocol that: coordinates with the NAN transceiver **202** to look, e.g., scan, for received frames and determine whether the received frames are NAN discovery frames; coordinates with the NAN transceiver **202** to transmit NAN discovery frames; forwards detected NAN discovery frames to the NAN discovery engine for decoding and filtering; and obtains and maintains synchronization in a NAN cluster within which the NAN device **200** is operating.

The memory **206** provides storage of electronic data used by the processing element **204** in performing its functionality. For example, the processing element **204** can use the memory **206** to load applications, save settings, and/or store files associated with the discovery of and communication with other NAN devices. In one embodiment, the memory **206** represents random access memory (RAM). In other

embodiments, the memory **206** represents volatile or non-volatile memory. For a particular embodiment, a portion of the memory **206** is removable. For example, the processing element **204** can use RAM to cache data while it uses a micro secure digital (microSD) card to store files associated with functionality performed in conjunction with discovering NAN devices.

The NAN transceiver **202** is a network interface that includes components which allow it to both send and receive NAN transmissions, such as NAN transmissions identified in the NANTSv1.0. In some embodiments, these transmissions are sent and received on Wi-Fi channel 6 (2.437 GHz) in the 2.4 GHz frequency band. In other embodiments, the transmissions are sent and received on Wi-Fi channel 44 (5.220 GHz) and/or channel 149 (5.745 GHz) in the 5 GHz frequency band. For described embodiments, NAN transmissions include NAN discovery beacon frames and NAN service discovery frames, such as publish and/or subscribe messages.

The alternate network interface **208** can include a transceiver configured to send and receive wireless transmissions that are not NAN transmissions. For some embodiments, the alternate network interface **208** includes a WLAN transceiver that enables the NAN device **200** to access the Internet using standards such as Wi-Fi or WiGig and/or a cellular transceiver that enables the NAN device **200** to engage in information exchange sessions, such as calls or message exchange sessions, with other communication devices using one or more cellular networks. An example Wi-Fi transceiver operates in accordance with an IEEE 802.11 (e.g., a, b, g, n, ac, or ad) standard to communicate with other devices in the 2.4 GHz, 3.65 GHz, 4.9 GHz, 5 GHz, 5.9 GHz, and/or 60 GHz frequency bands. An example cellular transceiver uses: 3G wireless technologies such as CDMA2000 and Universal Mobile Telecommunications System (“UMTS”) networks; 4G technologies such as Long-Term Evolution (LTE) and WiMAX; or 5G technologies.

For other embodiments, the alternate network interface **208** enables the NAN device **200** to establish direct links, short-range links, or otherwise engage in direct communications with another communication device without using an intermediary device. Additionally, the alternate network interface **208** can facilitate a wired connection with another communication device.

The user interface **212** represents a set of one or more components that allow for communication between the NAN device **200** and a user, owner, and/or programmer of the NAN device **200**. In some embodiments, the user interface **212** includes an input component, such as a keypad, which allows an individual to enter data into the NAN device **200**. A user, for example, might use the input component **212** to provide an application executing on the NAN device **200** with criteria by which particular services in which the user is interested may be identified. In other embodiments, the user interface **212** includes an output component, such as a display or speaker, which allows an individual to receive information from the NAN device **200**. The NAN device **200** might present notifications of available services for which the user has indicated interest. For additional embodiments, the user interface **212** includes both an input component and an output component, which allow for a bi-directional flow of information between the user and the NAN device **200**. The NAN device **200**, for example, might include a touchscreen configured for displaying images and text and also for receiving tactile input.

The power supply **210** represents a power source that supplies electric power to the device components **202**, **204**,

206, **208**, **212**, **214**, as needed, during the course of their normal operation. The power is supplied to meet the individual voltage and load requirements of the device components **202**, **204**, **206**, **208**, **212**, **214** that draw electric current.

For some embodiments, the power supply **210** is a wired power supply that provides direct current from alternating current using a full- or half-wave rectifier. For other embodiments, the power supply **210** is a battery that powers up and runs a portable NAN device. For a particular embodiment, the battery **210** is a rechargeable power source. A rechargeable power source for a NAN device is configured to be temporarily connected to another power source external to the NAN device to restore a charge of the rechargeable power source when it is depleted or less than fully charged. In another embodiment, the battery **210** is simply replaced when it no longer holds sufficient charge.

A detailed description of the functionality of a first communication device, taken in this example to be the NAN device **104** shown in FIG. 1, using the components shown in FIG. 2 is provided with reference to FIGS. 3 and 5. FIG. 3 shows a logical flow diagram illustrating a method **300** performed by the NAN device **104**, for instance, for performing NAN scanning on behalf of a second communication device, taken in this example to be the NAN device **102**. The NAN device **104** can perform the method **300** relative to one other NAN device or relative to multiple NAN devices for which the NAN device **104** has a common network connection.

At block **302**, the NAN device **104** detects a common network connection with the NAN device **102**. For example, the NAN device **104** detects that it is connected to the same Wi-Fi network as the NAN device **102**. For instance, the laptop **104** and smartphone **102** of a user are connected, as indicated at **126** and **124**, respectively, to the Wi-Fi network **130** of a local library. The smartphone **102** and laptop **104** exchange messages through the Wi-Fi network **130** which enable the communication devices **102** and **104** to know that they are connected to the same Wi-Fi network **130**. For another example, the laptop **104** and smartphone **102** have a direct, e.g., USB, BLE, Wi-Fi Direct, TDLIS, etc., connection, which the NAN device **104** detects.

Since it was determined **302** that both communication devices **102** and **104** have a common network connection, the NAN device **104** determines **310** to perform a surrogate NAN scanning role relative to the NAN device **102**. In other words, the NAN device **104** determines **310** to and performs **314** NAN scanning on behalf of the NAN device **102**. The NAN device **104** performing NAN scanning “on behalf” of the NAN device **102** means that, during a time that the NAN device **102** suppresses NAN scanning, the NAN device **104** searches for a NAN transmission from another NAN device which will trigger the NAN device **104** to report back to the NAN device **102**.

Presentation **502** of FIG. 5 illustrates the NAN device **104** performing NAN scanning **554** on behalf of the NAN device **102**. In this particular example, the NAN device **104** sends out NAN discovery beacon frames **552** and performs unsuppressed and continuous NAN scanning **554** between the NAN discovery beacon frames **552**. Continuous NAN scanning occurs without interruption, notwithstanding the duration of NAN discovery beacon frame transmissions, or other NAN transmissions, for which NAN scanning may briefly cease. In presentation **502**, for example, NAN scanning **554** is continuous, occurring at every time a NAN discovery beacon frame **552**, or other NAN frame, is not being transmitted. For embodiments in accordance with the NANTSv1.0, the interframe time intervals between the

NAN discovery beacon frames **552** are between 50 to 200 TUs, and the scanning time intervals **554** refer to continuous NAN scanning blocks between the NAN discovery beacon frames **552**.

For one embodiment, the NAN device **104** determines **310** to perform the NAN scanning on behalf of the second communication device **102** based on at least one parameter. Namely, at a block **304**, the NAN device **104** determines at least one parameter for the NAN devices **102** and **104**. The one or more parameters alone or in combination can include, but are not limited to, power capability, priority, and transceiver capability. For example, the NAN devices **102** and **104** exchange the parameters; the NAN device **104** receives the parameters from the NAN device **102**; and/or the NAN device **102** and/or **104** derives the parameters. These can be parameters stored in the NAN devices **102** and/or **104** such as priority and transmit power or parameters determined real-time such as power capability, priority, and received signal strength.

Power capability means the power available to a communication device to operate, whether from an internal or external power source or both. Priority indicates a preference of one communication device over another communication device. Such priority can be based on, for instance; the type of communication device, e.g., a smartphone has a higher priority than a tablet; a priority set by a user of the communication device; a factory set preference; an algorithm to determine priority based on current usage, e.g., a tablet is assigned a higher priority when video is playing on the tablet, or the smartphone is assigned a higher priority during an active voice call; etc. Transceiver capability concerns for instance, quality indicators for the transceiver's operation such as transmit power, transmit range, receiver sensitivity, and received signal strength, to name a few.

The NAN device **104** participates **306** in a ranking process based on the at least one parameter to relatively rank the NAN devices **102** and **104** as to which communication device performs the surrogate NAN scanning role and which communication device performs the subordinate scanning role. The ranking process can be based on one or multiple parameters and can use any suitable algorithm.

For one example, as a result of the ranking process **306** based on power capability as a parameter, the NAN device **104** determines **310** to perform NAN scanning on behalf of the NAN device **102** based on determining that the NAN device **104** has a higher power capability than the NAN device **102**. For instance, power capability can be determined based on one or more of battery capacity, instantaneous drain, remaining battery charge, whether connected to a wall socket or not, etc. In one example scenario, the NAN device **104** is connected to wall socket, while the NAN device **102** is not; so the NAN device **104** performs the surrogate NAN scanning role. In another example scenario, the NAN device **104** has more remaining battery charge than the NAN device **102**; so the NAN device **104** performs the surrogate NAN scanning role. For another example scenario, the NAN device **102** is a lower-powered paired smaller device (e.g., a smartwatch, smart glasses, etc.) to the NAN device **104**; so the NAN device **104** performs the surrogate NAN scanning role.

For another example, as a result of the ranking process **306** based on power capability as a parameter, the NAN device **104** determines **310** to perform NAN scanning on behalf of the NAN device **102** based on determining that the NAN device **104** has a lower power capability than the NAN device **102**. In one example scenario, the remaining battery charge of the NAN device **104** falls below a threshold

battery charge, for instance 25%. The NAN device **104** is, thereby, selected to perform the surrogate NAN scanning role to preserve the remaining battery charge of the NAN device **102**, which is above the threshold battery charge.

For another example, as a result of the ranking process **306** based on priority as a parameter, the NAN device **104** determines **310** to perform NAN scanning on behalf of the NAN device **102** based on determining that the NAN device **104** has a lower priority than the NAN device **102**. For one example scenario, the tablet or laptop **104** and smartphone **102** of a user are connected to the Wi-Fi network **130** at the library but neither device is connected to a wall charger. The user selects the smartphone **102** as a higher priority device to preserve the battery life of the smartphone **102** for use after leaving the library. Accordingly, the NAN device **104** performs the surrogate NAN scanning role. Alternatively, the tablet **104** is automatically selected as having a lower priority than the tablet **102** by virtue of the types of device.

For another example, as a result of the ranking process **306** based on transceiver capability as a parameter, the NAN device **104** determines **310** to perform NAN scanning on behalf of the NAN device **102** based on determining that the NAN device **104** has a higher transceiver capability than the NAN device **102**. For one example scenario, where the transceiver for the NAN device **104** has a longer transmit range or transmit power capability than the NAN device **102**, the NAN device **104** determines the NAN device **104** to have a higher transceiver capability. Additionally, where the transceiver for the NAN device **104** has a higher received signal strength or receiver sensitivity than the NAN device **102**, the NAN device **104** determines the NAN device **104** to have a higher transceiver capability.

For another example, either no ranking process is performed or the ranking process at **306** indicates that the NAN devices **102** and **104** have equal or substantially similar parameters and no relative ranking is possible. For this example, the NAN device **104** determines **310** to perform the NAN scanning on behalf of the NAN device **102** based on a random or pseudorandom selection. For one example scenario, both devices **102** and **104** are configured with a random number generator or a pseudo-random number generator to use in performing **308** a random or pseudo-random selection. The resultant numbers from these generators, thereby, determine which device performs the surrogate NAN scanning role and which device performs the subordinate NAN scanning role. For instance, based on a particular algorithm, the NAN device **104** determines **310** to perform the surrogate NAN scanning role when it generates the higher number. Alternatively, the NAN device **104** determines **310** to perform the surrogate NAN scanning role when it generates the lower number.

While performing **314** the NAN scanning on behalf of the NAN device **102**, the NAN device **104**, at block **316**, looks for a NAN transmission. The NAN device **104** continues in this surrogate NAN scanning role until detecting a NAN transmission, at which time the NAN device **104** notifies **318** the NAN device **102** and discontinues the surrogate NAN scanning role. For various embodiments, the NAN device **104** determining the detected transmission is a NAN transmission includes determining that the detected transmission has an information element identifying the detected transmission as a NAN transmission.

In some embodiments, the information element includes an organization unit identifier (OUI) which uniquely identifies a vendor, manufacturer, or other organization associated with the detected transmission. The OUI, in turn, includes an indication which identifies the detected trans-

11

mission as a NAN transmission, for instance, a hexadecimal value used in a particular field or data location of the OUI. For one embodiment, the information element is a NAN IE, incorporating NAN attributes, which is carried with NAN discovery beacon frames. When the NAN device **104** receives a NAN discovery beacon frame as a detected transmission, the NAN device **104** determines from a hexadecimal value in an OUI-Type field that the detected transmission is a NAN discovery beacon frame.

For some embodiments, the NAN device **104** determining the detected transmission is a NAN transmission includes determining that the detected transmission is part of a set of reoccurring transmissions having a periodicity of between 50 and 200 TUs. The detected transmission, for instance, is a NAN discovery beacon frame which is part of a set of periodically reoccurring NAN discovery beacon frames being transmitted by the NAN device **128** in a pattern analogous to that illustrated in presentation **504** of FIG. 5.

In accordance with the NANTSv1.0, NAN discovery beacon frames have a transmission periodicity of between 50 and 200 TUs. This is the time of transmission reoccurrence, or the interframe time interval, which is the same as the reception periodicity or the time between the reception of successive NAN discovery beacon frames. If the NAN device **104** measures a periodicity of less than 50 TUs or greater than 200 TUs, then the NAN device **104** determines the detected transmission is not a NAN discovery beacon frame. If, on the other hand, the NAN device **104** measures a periodicity of between 50 and 200 TUs, then the NAN device **104** determines the detected transmission is a NAN transmission. In a particular embodiment, the NAN device **104** further decodes the OUI of the NAN transmission to verify the detected transmission is a NAN transmission.

As illustrated in the presentation **502** of FIG. 5, the NAN device **104** performs NAN scanning **554** for the NAN device **102** (which has suppressed NAN scanning). Upon detecting a frame **556** that the NAN device **104** determines is a NAN transmission, the NAN device **104** sends **318** a notification **566** to the NAN device **102**. The notification **566** can be any suitable communication or messaging to the NAN device **102**.

For one example where the NAN devices **102** and **104** are connected to the same Wi-Fi network **130**, the NAN devices **102** and **104** implement the Wake on Wireless LAN (WoW-LAN) standard, whereby the NAN device **104** broadcasts a magic packet **566** that can be detected by the NAN device **102** as a notification to trigger the NAN device **102** to discontinue suppressing NAN scanning. Similarly, where the NAN devices **102** and **104** are connected to the same wired LAN network, the NAN devices **102** and **104** can implement the Wake-on-LAN (WoL) standard, whereby the NAN device **104** sends a magic packet **566** to trigger the NAN device **102** to discontinue suppressing NAN scanning.

For one embodiment, the NAN device **104** sends **318** the notification **566** to the NAN device **102** upon detecting any type of NAN transmission **556**. Alternatively, the NAN device **104** sends **318** the notification **566** to the NAN device **102** only upon detecting a NAN transmission **556** that identifies a service sought by the NAN device **102**. Thus in this embodiment, block **316** (detecting the NAN transmission) is satisfied only when a NAN transmission is detected that identifies the particular service sought by the second communication device **102**.

To support this embodiment, the NAN device **104** receives **312** an indication of a service sought by the NAN device **102**. For example, a document is queued by the user or an application for printing, and the NAN device **104**

12

receives **312** an indication that the NAN device **102** seeks printing service. For one example, the NAN device **102** creates and sends to the NAN device **104** a NAN transmission, such as a NAN discovery beacon frame or a NAN service discovery frame, which includes a service ID or service descriptor attribute that identifies the printing services sought. Any other suitable messaging can be used to indicate to the NAN device **104** the particular service or services sought by the NAN device **102**.

For a particular embodiment, the NAN device **104** properly detects a NAN transmission when it detects a NAN discovery beacon frame that identifies the service sought by the second communication device. For example, while scanning **554**, the NAN device **104** detects a NAN discovery beacon frame **556** from a printer device **128** while the user is still in the library or when the user returns home. Upon decoding and filtering the NAN discovery beacon frame **556**, the NAN device **104** matches a service ID in the NAN discovery beacon frame **556** with a service ID provided by the NAN device **102**. Accordingly, the NAN device **104** notifies **318** the NAN device **102** and discontinues the surrogate NAN scanning role.

For another embodiment, the NAN device **104** properly detects a NAN transmission when it detects a NAN service discovery frame that identifies the service sought by the second communication device. For one implementation scenario, the NAN device **104** passively scans for a NAN service discovery frame that indicates, e.g., using a service ID or service descriptor attribute, the printing service sought by the NAN device **102**. For instance, while scanning **554**, the NAN device **104** detects a NAN discovery beacon frame sent by a NAN device **110** performing a master role for a nearby NAN cluster **108**. The NAN device **104** joins the NAN cluster **108** and passively scans for a NAN service discovery frame that includes a publish message which identifies a printing service.

Alternatively, the NAN device **104** actively scans **554** for the publish message. For this implementation scenario, the NAN device **104** sends a subscribe message that identifies the service sought by the second communication device, while joined to the NAN cluster **108**. Accordingly, the NAN device **104** properly detects a NAN transmission when it detects a NAN service discovery frame that includes a publish message received in response to the subscribe message. The NAN device **104** can use its own internal NAN discovery engine to create the subscribe message or forward a subscribe message created and provided by the NAN device **102**.

A detailed description of the functionality of a second communication device, e.g., the NAN device **102** shown in FIG. 1, using the components shown in FIG. 2 is provided with reference to FIGS. 4 and 5. FIG. 4, for example, shows a logical flow diagram illustrating a method **400** performed by a NAN device, taken to be the NAN device **102**, for suppressing NAN scanning to allow another NAN device, in this example the NAN device **104**, to perform the NAN scanning on its behalf. For some embodiments, the NAN device **102** provides **412** an indication of a service sought by the NAN device **102** for which the NAN device **104** searches.

The NAN device **102** detects **402** a common connection with the NAN device **104**, and determines **410** to suppress NAN scanning, which NAN device **102** performs at block **414**, thereby performing a subordinate NAN scanning role. For one embodiment, the NAN device **102** determines **404** at least one parameter, such as power capability, priority, and/or transceiver capability, for the NAN devices **102** and

104 and participates 406 in a ranking process based on the at least one parameter to relatively rank the NAN devices 102 and 104. The NAN device 102, thereby, determines 410 to suppress NAN scanning based on the results of the relative ranking. For another embodiment, the NAN device 102 performs 408 a random or pseudo-random selection by which the NAN device 102 determines 410 to suppress NAN scanning. Functionality represented by blocks 402, 404, 406, 408, and 410 can be similarly performed as the functionality represented by the corresponding blocks 302, 304, 306, 308, and 310 (of FIG. 3), respectively, the description of which is not repeated here for brevity.

The NAN device 102 suppresses 414 NAN scanning and monitors 418 for a notification that indicates a detected NAN transmission, such as monitoring for a magic packet or other suitable message. When, at block 420, such a notification (e.g., notification 566 of FIG. 5) is detected, the NAN device 102 discontinues 422 suppressing NAN scanning. For an embodiment, the NAN device 102 begins or returns to sending NAN discovery beacon frames 562 between which the NAN device 102 continuously scans 564 for NAN transmissions to detect the NAN transmissions 556 which were detected by the NAN device 104.

Suppressing NAN scanning, indicated in block 414, means that scanning for NAN transmissions by the NAN transceiver 202 and processor 204 is curtailed either partially or completely in comparison to when NAN scanning is not suppressed. For some embodiments, NAN transmitting is also suppressed, as indicated in block 416, when suppressing the NAN scanning. This has the benefit of further reducing the number of NAN transmissions sent over the same channel. Turning to FIGS. 5 and 6, suppressing NAN scanning and NAN transmitting is described in further detail. The presentation 504 shown in FIG. 5, described previously, graphically represents unsuppressed NAN scanning by the NAN device 102. By contrast to the presentation 504, the presentation 502 of FIG. 5 and the presentations 606 and 608 of FIG. 6 illustrate suppressed NAN scanning.

For some embodiments, suppressing NAN scanning includes disabling NAN scanning. This is illustrated in presentation 502, which shows NAN scanning is discontinued in that it is no longer performed by the NAN transceiver 202 and processor 204 of the NAN device 102 before receiving the notification 566. Also absent from presentation 502 are any NAN discovery beacon frames transmitted by the NAN transceiver 202. This reflects an embodiment which further includes disabling a first type of NAN transmission, in this case disabling transmitting NAN discovery beacon frames, while suppressing NAN scanning. In other instances, the NAN device 102 disables transmitting NAN service discovery frames while suppressing NAN scanning. For some embodiments, NAN transmitting is disabled altogether while NAN scanning is suppressed.

For other embodiments, suppressing NAN scanning includes reducing NAN scanning as compared to unsuppressed NAN scanning. In such embodiments, NAN scanning is not completely curtailed. Presentation 606 illustrates ways in which the NAN device 102 can partially suppress NAN scanning and NAN transmitting. As compared to presentation 504, for which no suppression occurs, every other NAN discovery beacon frame is omitted from presentation 606, along with the scanning time interval that immediately followed the omitted NAN discovery beacon frames. For scanning blocks 674 and NAN discovery beacon frames 672 that remain in presentation 606, the scanning time intervals 678 are of the same length as the scanning time intervals 588, but the interframe time intervals 676 have

doubled as compared to the interframe time intervals 586 for presentation 504. Accordingly, this embodiment illustrates suppressing NAN transmissions by reducing a rate of sending a first type of neighborhood awareness networking transmission.

In other embodiments, NAN scanning and NAN transmitting is suppressed by omitting different combinations of NAN discovery beacon frames and associated scanning blocks from the unsuppressed sequence in different patterns. Labeling the sequence of presentation 504, without omissions, as successive positive integers "1-2-3-4-5," and the sequence of every other NAN discovery beacon frame 672 and scanning block 674, illustrated in presentation 606, as the sequence of successive odd integers "1-3-5-7-9," for example, other embodiments of suppressed scanning and transmitting are represented by sequences "1-4-7-10-13," "1-2-4-5-7," and "1-4-5-8-9." Other embodiments represent additional sequences associated with suppressing NAN scanning and NAN transmitting.

For some embodiments, reducing NAN scanning includes NAN scanning during scanning time intervals which are discontinuous in time. Viewing the suppressed NAN scanning and NAN transmitting illustrated in presentation 606 differently, the spacing of the NAN discovery beacon frames 582 and NAN scanning blocks 584 of the unsuppressed presentation 504 is increased to yield the suppressed presentation 606. This increases the interframe time interval from that indicated at 586 to that indicated at 676. The scanning time interval 678 for scanning block 674, however, is the same as the scanning time interval 588 for scanning block 584. This results in suppressed NAN scanning that is discontinuous. The scanning blocks 674 are separated from one another by approximately the difference in time between the interframe time interval 676 and the scanning time interval 678.

Discontinuous NAN scanning occurs if there are periods of time when a NAN device both is not sending a NAN transmission and not performing NAN scanning. NAN scanning is discontinuous in presentation 608, for example. During the latter portion of time interval 690, the NAN device 102 is not performing NAN scanning or sending a NAN transmission. A scanning time interval 688, for instance, is a discontinuous scanning time interval, whereas the scanning time interval 588 is a continuous scanning time interval.

In presentation 608, discovery beacon frames 682 are distributed with an interframe time interval 686, which is similar to the interframe time interval 676 for presentation 606. In presentation 608, however, a first type of NAN transmission, in this case the transmission of the NAN discovery beacon frames 682 is further suppressed in that the NAN device 102 transmits them at a reduced power level, or reduced transmit power, as compared to the transmission of the NAN discovery beacon frames 672 or 582. Scanning is also further suppressed in that scanning blocks 684 have the scanning time interval 688, which is shorter compared to the scanning time intervals 678 and 588 for scanning blocks 674 and 584, respectively. Thus for this embodiment, suppressing NAN scanning includes reducing a scanning time interval during which the NAN scanning occurs.

For various embodiments, NAN scanning and NAN transmitting is reduced, and thereby suppressed or further suppressed, by increasing interframe time intervals. NAN scanning is also reduced, and thereby suppressed or further suppressed, by decreasing scanning time intervals. Addition-

15

ally, NAN transmitting is also reduced, and thereby suppressed or further suppressed, by decreasing a transmission power level.

In one embodiment, one or more of the discontinuous scanning time intervals when NAN scanning is suppressed is shorter in time than an interframe time interval between NAN discovery beacon frames when NAN scanning is not suppressed. This is made evident by comparing presentation 608 to presentation 504. In presentation 608, the scanning time interval 688 is shorter than the interframe time interval 586 of presentation 504.

In another embodiment, one or more of the discontinuous scanning time intervals when NAN scanning is suppressed is shorter than one or more continuous scanning time intervals when NAN scanning is not suppressed. This is also made evident by comparing presentation 608 to presentation 504. In presentation 608, the scanning time interval 688 is shorter than the scanning time interval 588 of presentation 504.

In further embodiments, the discontinuous scanning time intervals are shorter than an interval of time separating the discontinuous scanning time intervals. This is illustrated in presentation 608 where the scanning time intervals 688 are shorter than an interval of time 690 separating the scanning blocks 684. For a particular embodiment, the discontinuous scanning time intervals 688 are 50 TUs or less in length, below the minimum length of time specified in the NANTSV1.0. In an embodiment having discontinuous scanning time intervals of different lengths, one or more of the discontinuous scanning time intervals is 50 TUs or less in length.

For some embodiments, reducing NAN scanning includes disabling passive NAN scanning while decreasing active NAN scanning. Active NAN scanning is reactionary scanning that occurs in anticipation of an expected response to a transmitted message. In accordance with the NANTSV1.0, for example, a NAN device may use NAN service discovery frames to actively look for availability of specific services. NAN service discovery protocol messages include publish and subscribe messages. A NAN device sends a subscribe message to solicit another NAN device to responsively transmit a publish message if response criteria are met. The NAN device 102 scanning for a response to a transmitted subscribe message exemplifies decreased active NAN scanning if the active NAN scanning occurs less frequently or on a shorter intervals of time as compared to when active NAN scanning is not being suppressed.

For other embodiments, reducing NAN scanning includes disabling active NAN scanning while decreasing passive NAN scanning. Passive NAN scanning is scanning that occurs without an expected response to a previously transmitted message. Scanning for NAN discovery beacon frames, for example, is passive NAN scanning because the NAN discovery beacon frames are not received in response to a message soliciting their transmission. Reduced NAN scanning consistent with these embodiments is illustrated by the scanning blocks 674 and 684 of presentations 606 and 608, respectively, provided that active NAN scanning is discontinued.

As mentioned earlier, when the NAN device 102 detects the notification 566 from the NAN device 104, then the NAN device 102 discontinues 422 suppressing NAN scanning. If NAN transmitting was also suppressed, as indicated at 416, then the NAN device 102 also discontinues suppressing NAN transmitting upon detecting the notification 566.

16

Discontinuing suppressing NAN scanning means restoring NAN scanning. If NAN scanning was discontinued in suppressing NAN scanning, then the NAN device 102 again continues to perform NAN scanning. For example, NAN scanning is restored from occurring as illustrated in presentation 502 back to occurring as illustrated in presentation 504. If NAN scanning was reduced in suppressing NAN scanning, then NAN scanning is again increased. For example, NAN scanning is restored from occurring as illustrated in presentation 606 or 608 back to occurring as illustrated in presentation 504.

Discontinuing suppressing NAN transmitting means restoring NAN transmitting. If NAN transmitting was discontinued in suppressing NAN transmitting, then the NAN device 102 again continues to perform NAN transmitting. For example, NAN transmitting is restored from occurring as illustrated in presentation 502 back to occurring as illustrated in presentation 504. If NAN transmitting was reduced in suppressing NAN transmitting, then NAN transmitting is again increased. For example, NAN transmitting is restored from occurring as illustrated in presentation 606 or 608 back to occurring as illustrated in presentation 504.

For yet another embodiment, suppressing 414 NAN scanning includes transitioning to a lower-power state from a higher-power state. Correspondingly, discontinuing 422 the suppressing of the NAN scanning includes transitioning from the lower-power state to the higher-power state. For one example, transitioning to a lower-power state includes putting the NAN device 102 into a “sleep” mode, whereby only the components needed to detect 420 the notification are provided with power. For instance, the NAN device 102 is powered only to the extent that it can detect magic packets from the NAN device 104. For another example, transitioning to a lower-power state includes disabling only NAN functionality on the NAN device 102 and leaving some other functionality implementing on the NAN device 102 such as Wi-Fi and cellular operations. Other methods of power-management can be performed in the NAN device 102 related to transitioning to the lower-power state. When transitioning to the higher-power state, the NAN device 102 restores full power to the device components or restores partial power above what is available in the lower-power state.

In the foregoing specification, specific embodiments have been described. However, one of ordinary skill in the art appreciates that various modifications and changes can be made without departing from the scope of the invention as set forth in the claims below. Accordingly, the specification and figures are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of present teachings.

The benefits, advantages, solutions to problems, and any element(s) that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as a critical, required, or essential features or elements of any or all the claims. The invention is defined solely by the appended claims including any amendments made during the pendency of this application and all equivalents of those claims as issued.

Moreover in this document, relational terms such as first and second, top and bottom, and the like may be used solely to distinguish one entity or action from another entity or action without necessarily requiring or implying any actual such relationship or order between such entities or actions. The terms “comprises,” “comprising,” “has,” “having,” “includes,” “including,” “contains,” “containing” or any other variation thereof, are intended to cover a non-exclusive

17

inclusion, such that a process, method, article, or apparatus that comprises, has, includes, contains a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. An element preceded by “comprises . . . a,” “has . . . a,” “includes . . . a,” or “contains . . . a” does not, without more constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that comprises, has, includes, contains the element. The terms “a” and “an” are defined as one or more unless explicitly stated otherwise herein. The terms “substantially,” “essentially,” “approximately,” “about” or any other version thereof, are defined as being close to as understood by one of ordinary skill in the art, and in one non-limiting embodiment the term is defined to be within 10%, in another embodiment within 5%, in another embodiment within 1% and in another embodiment within 0.5%. The term “coupled” as used herein is defined as connected, although not necessarily directly and not necessarily mechanically. A device or structure that is “configured” in a certain way is configured in at least that way, but may also be configured in ways that are not listed.

It will be appreciated that some embodiments may be comprised of one or more generic or specialized processors (or “processing devices”) such as microprocessors, digital signal processors, customized processors and field programmable gate arrays (FPGAs) and unique stored program instructions (including both software and firmware) that control the one or more processors to implement, in conjunction with certain non-processor circuits, some, most, or all of the functions of the method and/or apparatus described herein. Alternatively, some or all functions could be implemented by a state machine that has no stored program instructions, or in one or more application specific integrated circuits (ASICs), in which each function or some combinations of certain of the functions are implemented as custom logic. Of course, a combination of the two approaches could be used.

Moreover, an embodiment can be implemented as a computer-readable storage medium having computer readable code stored thereon for programming a computer (e.g., comprising a processor) to perform a method as described and claimed herein. Examples of such computer-readable storage mediums include, but are not limited to, a hard disk, a CD-ROM, an optical storage device, a magnetic storage device, a ROM (Read Only Memory), a PROM (Programmable Read Only Memory), an EPROM (Erasable Programmable Read Only Memory), an EEPROM (Electrically Erasable Programmable Read Only Memory) and a Flash memory. Further, it is expected that one of ordinary skill, notwithstanding possibly significant effort and many design choices motivated by, for example, available time, current technology, and economic considerations, when guided by the concepts and principles disclosed herein will be readily capable of generating such software instructions and programs and ICs with minimal experimentation.

The Abstract of the Disclosure is provided to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in various embodiments for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive

18

subject matter lies in less than all features of a single disclosed embodiment. Thus the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separately claimed subject matter.

We claim:

1. A method performed by a first communication device, the method comprising:

detecting, via a first network interface of the first communication device, a common network connection with a second communication device, wherein the first network interface is associated with a first communication protocol;

determining to perform neighborhood awareness networking scanning, via a second network interface of the first communication device, on behalf of the second communication device in response to a determination that the second communication device is a subordinate device to the first communication device, wherein the second network interface is different than the first network interface and the second network interface is associated with a second communication protocol different than the first communication protocol;

detecting, via the second network interface of the first communication device, a neighborhood awareness networking transmission while performing the neighborhood awareness networking scanning; and

in response to the detecting of the neighborhood awareness networking transmission via the second network interface:

notifying, via the first network interface of the first communication device, the second communication device of the detected neighborhood awareness networking transmission, and

discontinuing the neighborhood awareness networking scanning on behalf of the second communication device.

2. The method of claim 1, wherein the determining to perform the neighborhood awareness network scanning on behalf of the second communication device is based on at least one parameter.

3. The method of claim 2, wherein the at least one parameter comprises power capability, and wherein the determining to perform the neighborhood awareness networking scanning is based on determining that the first communication device has a higher power capability than the second communication device.

4. The method of claim 2, wherein the at least one parameter comprises power capability, and wherein the determining to perform the neighborhood awareness networking scanning is based on determining that the first communication device has a lower power capability than the second communication device.

5. The method of claim 2, wherein the at least one parameter comprises priority, and wherein the determining to perform the neighborhood awareness networking scanning is based on determining that the first communication device has a lower priority than the second communication device.

6. The method of claim 2, wherein the at least one parameter comprises transceiver capability, and wherein the determining to perform the neighborhood awareness networking scanning is based on determining that the first communication device has a higher transceiver capability than the second communication device.

19

7. The method of claim 1, wherein the detected neighborhood awareness transmission identifies a service sought by the second communication device.

8. The method of claim 7, wherein the detecting of the neighborhood awareness networking transmission comprises detecting a neighborhood awareness networking service discovery frame that identifies the service sought by the second communication device.

9. The method of claim 8, wherein the detected neighborhood awareness networking service discovery frame comprises a publish message received in response to transmitting a subscribe message that identifies the service sought by the second communication device.

10. The method of claim 1, wherein the determining to perform the neighborhood awareness network scanning on behalf of the second communication device is based on a random or pseudorandom selection.

11. A method performed by a second communication device, the method comprising:

detecting, via a first network interface of the second communication device, a common connection with a first communication device, wherein the first network interface is associated with a first communication protocol;

suppressing neighborhood awareness networking scanning, via a second network interface of the second communication device, in response to a determination that the second communication device is a subordinate device to the first communication device, wherein the second network interface is different than the first network interface and the second network interface is associated with a second communication protocol different than the first communication protocol;

receiving, via the first network interface of the second communication device, a notification from the first communication device, wherein the notification indicates a detected neighborhood awareness networking transmission; and

discontinuing the suppressing of the neighborhood awareness networking scanning in response to the receiving of the notification.

12. The method of claim 11 further comprising participating in a ranking process to determine a relative ranking between the first and second communication devices based on at least one parameter, and wherein the suppressing of the neighborhood awareness networking scanning is based on the relative ranking.

13. The method of claim 11, wherein the suppressing of the neighborhood awareness networking scanning comprises disabling the neighborhood awareness networking scanning.

14. The method of claim 11, wherein the suppressing of the neighborhood awareness networking scanning comprises reducing a scanning time interval during which the neighborhood awareness networking scanning occurs.

20

15. The method of claim 11, wherein:

the suppressing of the neighborhood awareness networking scanning comprises transitioning to a lower-power state from a higher-power state; and

the discontinuing of the suppressing of the neighborhood awareness networking scanning comprises transitioning from the lower-power state to the higher-power state.

16. The method of claim 11 further comprising suppressing at least one type of neighborhood awareness networking transmission when suppressing the neighborhood awareness networking scanning.

17. The method of claim 16, wherein the suppressing of the at least one type of neighborhood awareness networking transmission comprises disabling a first type of neighborhood awareness networking transmission.

18. The method of claim 16, wherein the suppressing of the at least one type of neighborhood awareness networking transmission comprises reducing a rate of sending a first type of neighborhood awareness networking transmission.

19. The method of claim 16, wherein the suppressing of the at least one type of neighborhood awareness networking transmission comprises reducing a transmit power for sending a first type of neighborhood awareness networking transmission.

20. A first communication device comprising:

a first network interface to:

form a common network connection with a second communication device, wherein the first network interface is associated with a first communication protocol;

a second network interface to:

receive a neighborhood awareness networking transmission, wherein the second network interface is different than the first network interface and the second network interface is associated with a second communication protocol different than the first communication protocol; and

a processor coupled to the first network interface and the second network interface, the processor to:

determine to perform a surrogate neighborhood awareness networking scanning role relative to the second communication device in response to a determination that the second communication device is a subordinate device to the first communication device;

detect, via the second network interface, the neighborhood awareness networking transmission while performing the surrogate scanning role; and

in response to the detecting of the neighborhood awareness networking transmission:

notify, via the first network interface, the second communication device of the detected neighborhood awareness networking transmission, and determine to discontinue the surrogate scanning role.

* * * * *